


P.C.B LAYOUT (front view)



Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:-20℃~70℃
 Operating force:3-20N
 Operating Life:5,000cycles

| ITEM | PART NAME | TER'NO. | QTY. | MATERIAL | FINISHING | REMARK |
|------|-----------|---------|------|-----------------|------------|--------|
| ③ | Spring | | 1 | SUS | Si Plating | |
| ② | Terminal | | 2 | Phosphor bronze | Au Plating | |
| ① | Housing | | 1 | Nylon | Black | |

| APPROVALS | | DATE | 东莞市颖鑫电子科技有限公司 | | |
|----------------|--------------|------------|---------------|--------------|--------------|
| DRAWN | JKUN.LU | 2013/11/11 | TITLE: | PHONE JACKES | |
| CHECKED | | | PART NO. | DC-060B | |
| APPROVALS | | | UNIT: mm | SCALE: 1:1 | PROJ: |
| TOLERANCES ARE | 30~以上: ±0.30 | ANGLE | DRAWING NO. | | SHEET 1 OF 1 |
| | 10~30 ±0.20 | ±2' | | | |
| | 5~10 ±0.15 | | | | |
| | ~ 5 ±0.10 | | | | |

| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
|---------|------|-------|--------------|---------|--------|--------|
| | A | | NEW | | | |